



1807 N. Bloomington St.
 Streator, IL 61364
 Ph: 815-672-3211 or 800-443-0843
 Fax: 815-672-1490
 E-Mail: sales@ustruckbody.com

Date:
 Quote #: STOCK
 Model: VA 14 96 90

Quantity: 1 / STOCK BODY

ALUMINUM RIVETLESS VAN BODY QUOTATION

LENGTH: 14' I.D.

WIDTH: 96" O.D.

HEIGHT: 84" I.D.

Construction:	(.040) Pre-painted white aluminum panels with high strength extruded aluminum (not steel) "Z" posts on 16" centers. Rivetless construction. Seven front wall posts (not five) for added strength and durability. Extruded aluminum front corner radius posts, (not roll formed) for maximum strength.
Roof:	(.060) Translucent roof panel with anti-snap roof bows on 24" centers, "Zephyr" 12" fuel saving roof radius design with heavy-duty cast aluminum (not plastic) corner castings.
Rear Frame:	12 Ga. Stainless steel, internally and externally reinforced, and gusseted at all stress points. <i>Stainless steel is now standard on all US Truck bodies.</i>
Side Door(s):	None.
Rear Door:	Standard plastic covered 3/4" plywood roll up, 88" wide x 78.5" high clear opening. Stainless steel rivets and "E" coated hardware.
Rear:	Choice of bumper or liftgate.
Grab Handle(s):	Curb side and road side on rear frame.
Rear Lighting:	Utilize OEM chassis tail lights.
Floor:	1-1/8" high quality domestic laminated hardwood
Cross members:	3" steel I-Beam cross members on 12" centers with full steel wheel pan support over wheel area.
Interior Sides:	Sides – Customer Choice
Interior Front:	Front – Customer Choice
Interior Ties:	Customer Choice

STOCK / PAGE 2

Scuff Plate:	Customer Choice
Lights:	Interior – One (1) dome light(s) with switch at rear, inside door on curbside. <i>Note: When switch is supplied by chassis OEM, dome light will be wired to factory switch in cab.</i> Exterior - per FMVSS - 108 with reflectors.
Undercoating:	Petroleum base undercoating applied, (not paint) full understructure.
Mounting:	Hardwood isolator with 5/8" zinc plated U-bolts installed through custom cut steel crush pipes between chassis frame. Structural steel channel anti-shift "side standards" welded to structural steel long sills. Complete factory mounting on drop shipped chassis with "U.S. Truck Body" or customer supplied mud flaps.
Understructure:	Unless noted below in ADDITIONAL FEATURES, this body is quoted and built for a single axle chassis. Tandem axle chassis require the <i>additional cost option</i> for our <i>Tandem Axle Reinforcement Package</i> .

Total Installed Price, F.O.B. Streator, IL: \$Call or Email

ADDITIONAL FEATURES INCLUDED IN THE ABOVE PRICING:

1. LED clearance lights